



MATERIALS

PRIMARY YARN POLYMER	Nylon
YARN CROSS SECTION	Diamond Monofilament
STANDARD COLOR	8641 Turf Green Cool
UV STABILIZED	Yes
FABRIC CONSTRUCTION	Tufted
SECONDARY YARN POLYMER THATCH	Texture Nylon
SECONDARY YARN COLOR	Green/Tan
PRIMARY BACKING	13/18 PET
COATING TYPE	Polyurethane
TEXTURIZED NYLON YARN	4,200/8
TEXTURIZED THATCH DENIER / ENDS	4,200/8
SUSTAINABILITY	100% Recyclable
WARRANTY PERIOD	10 years

FINISH FABRIC

ENGLISH SYSTEM

ASTM STANDARDS

NOMINAL SPECIFICATION	VALUE	UNITS	METHOD
PILE HEIGHT (NOMINAL)	11/4	inches	D-5823
FACE WEIGHT	54	oz/yd ²	D-5848
TOTAL FABRIC WEIGHT	81	oz/yd ²	D-5848
PRIMARY BACKING WEIGHT	7	oz/yd ²	D-5848
SECONDARY COATING WEIGHT	20	oz/yd ²	D-5848
TUFT BIND	>8	lbs.	D-1335
GRAB TEAR STRENGTH (AVERAGE)	>200	lbs.	D-5034
LEAD CONTENT	<50	ppm	F-2765
TOTAL YARN LINEAR DENSITY	8,400	Denier	D-1577
ELONGATION TO BREAK	>60	%	D-2256
YARN BREAKING STRENGTH	>19	lbs.	D-2256
YARN MELTING POINT	420	F°	D-7138
STITCH RATE	6.5	Spi.	D-5793
MACHINE GAUGE	3/8	inch	D-5793
FLAMMABILITY	Pass		D-2859
WATER PERMEABILITY	>30	in/hr	DIN 18-035
FABRIC WIDTH	15	ft	None

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are ± 5%.