







MATERIALS

WARRANTY PERIOD	9 years	
SUSTAINABILITY	100% Recyclable	
TEXTURIZED THATCH DENIER /ENDS	4,200/8	
POLYETHYLENE YARN DENIER / ENDS	8,000/1	
COATING TYPE	5mm Polyurethane Foam	
PRIMARY BACKING	13/18 PET	
SECONDARY YARN COLOR	Green	
SECONDARY YARN POLYMER THATCH	Texture Nylon	
FABRIC CONSTRUCTION	Tufted	
UV STABILIZED	Yes	
STANDARD COLOR	Meadow Green	
YARN CROSS SECTION	Slit-Film	
PRIMARY YARN POLYMER	Polyethylene	

FINISH FABRIC

ENGLISH SYSTEM

ASTM STANDARDS

NOMINAL SPECIFICATION	VALUE	UNITS	METHOD
PILE HEIGHT(NOMINAL)	3/4"	inches	D-5823
FACE WEIGHT	58	oz/yd2	D-5848
TOTAL FABRIC WEIGHT	123	oz/yd2	D-5848
PRIMARY BACKING WEIGHT	7	oz/yd2	D-5848
SECONDARY COATING WEIGHT	58	oz/yd2	D-5848
TUFT BIND	>8	lbs.	D-1335
GRAB TEAR STRENGTH(AVERAGE)	>200	lbs.	D-5034
LEAD CONTENT	<50	ppm	F-2765
TOTAL YARN LINEAR DENSITY	6,100	Denier	D-1577
ELONGATION TO BREAK	>60	%	D-2256
YARN BREAKING STRENGTH	>19	lbs.	D-2256
YARN MELTING POINT	248	F°	D-7138
STITCH RATE	6.7	Spi.	D-5793
MACHINE GAUGE	3/16	inch	D-5793
FLAMMABILITY	Pass		D-2859
WATER PERMEABILITY	>30	in/hr	DIN 18-035
FABRIC WIDTH	15	ft	None

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are \pm 5%.